

RoadKit

For sliding gates up to 200kg

Compartment for the pull-out control unit, protected by casing, and for buffer batteries

Aluminium release handle for easy opening

Sturdy: pressure die-cast aluminium base and release, with epoxy painting



Kit for the automation of sliding gates weighing up to 200kg and up to 5m length. Irreversible gear motor with electromechanical limit switches.

Practical

Built-in control unit, can be connected by means of a simple connector and can be housed directly inside the motor; incorporated radio card, compatible with the Nice Flo and Smilo systems: 150 transmitters can be entered!

Advanced

The speed, strength and pause can all be adjusted.

Intelligent

Thanks to the obstacle detection system and automatic programming of the working times. Self-diagnosis by means of a flashing light.

Safe

Acceleration and deceleration can be adjusted at the beginning and end of each opening and closing manoeuvre.

Rapid and quiet

Gear motor 24Vdc on bearings; very quick and quiet.

Technical specifications	ROAD200
Power (Vac 50/60Hz)	230
Max. powered absorbed (VA)	150
Protection level (IP)	44
Nominal torque (Nm)	3,3
Max. torque (Nm)	6
Speed* (m/s)	0.14÷0.26
Max gate weight (kg)	200
Working temp. (°C Min/Max)	-20 ÷ +50
Insulation class	1
Work cycle* (cycles/day)	30
Weight (kg)	12

* This value changes according to the gate weight

Accessories included in the kit:

FLO2R-S

1 transmitter
433.92MHz,
2 channels

MOF

1 pair of photocells
for outdoor
installation

MOSE

1 key selector switch
for outdoor
installation

LUCYB

1 flashing light
with integrated aerial

TS

1 signboard

RDKCE

Kit for sliding gates
up to 200kg

